

## Air Conditioner Product Line



HC = High Capacity Series  
 CS = Compact Design Series  
 NE = Narrow Edge 12" Wide Series  
 WF = Wide Format Design Series

- All units are available in NEMA Type 12, 4 and 4X
- NEMA 4X available in 304 (2 finishes) and 316
- Hazardous Location Systems available for Class 1, Div 2, Groups B, C, D

Model	BTU/Hour	Voltage/ Phase/ Hz.	Running Amps	Maximum Ambient Temp.	Maximum Integrated Heat in Watts	H x W x D	Ship Weight
NE010126	1000	120/1/60	3.44	125°F	NA	22" x 11.8" x 8.5"	57
NE010236	1000	230/1/60	2.06	125°F	NA	22" x 11.8" x 8.5"	57
NE015126	1500	120/1/60	3.49	125°F	NA	22" x 11.8" x 8.5"	57
NE015236	1500	230/1/60	2.06	125°F	NA	22" x 11.8" x 8.5"	57
NE020126	2000	120/1/60	3.76	131°F	1000	32" x 11.8" x 9.5"	70
NE020486	2000	480/1/60	1.8	131°F	1000	38" x 11.8" x 9.5"	110
CS020126	2000	120/1/60	3.76	125°F	500	20" x 10" x 10"	60
CS020236	2000	230/1/60	2.1	125°F	500	20" x 10" x 10"	60
NE030126	3000	120/1/60	5.15	131°F	1000	32" x 11.8" x 9.5"	70
NE030486	3000	480/1/60	1.4	131°F	1000	38" x 11.8" x 9.5"	110
NE040126	4000	120/1/60	5.53	131°F	1000	32" x 11.8" x 9.5"	70
NE040236	4000	230/1/60	3.26	125°F	1000	32" x 11.8" x 9.5"	70
NE040486	4000	480/1/60	1.7	125°F	1000	38" x 11.8" x 9.5"	110
NE050126	5000	120/1/60	7.7	125°F	1000	36" x 11.8" x 15.1"	100
NE050236	5000	230/1/60	4.07	125°F	1000	36" x 11.8" x 15.1"	100
NE050486	5000	480/1/60	2.1	125°F	1000	44.63" x 11.8" x 15.1"	140
NE060126	6000	120/1/60	7.83	125°F	1000	36" x 11.8" x 15.1"	100
NE060236	6000	230/1/60	4.95	125°F	1000	36" x 11.8" x 15.1"	100
NE060486	6000	480/1/60	2.6	125°F	1000	44.63" x 11.8" x 15.1"	140
WF060126	6000	120/1/60	13.3	125°F	1000	36.8" x 19" x 10.5"	100
WF060236	6000	230/1/6	6.8	125°F	1000	36.8" x 19" x 10.5"	100
NE080126	8000	120/1/60	8.7	125°F	1000	36" x 11.8" x 15.1"	100
NE080236	8000	230/1/60	5.05	125°F	1000	36" x 11.8" x 15.1"	100
NE080486	8000	480/1/60	2.8	125°F	1000	44.63" x 11.8" x 15.1"	140
WF080126	8000	120/1/60	12.85	125°F	1000	36.8" x 19" x 10.5"	100
WF080236	8000	230/1/60	9.0	125°F	1000	36.8" x 19" x 10.5"	100
HC100126	10,000	120/1/60	16.3	125°F	1500	48" x 15.9" x 15.1"	145
HC100236	10,000	230/1/60	8.12	125°F	1500	48" x 15.9" x 15.1"	145
HC100486	10,000	480/1/60	4.5 approx	125°F	1500	56.6" x 15.9" x 15.1"	205
HC120126	12,000	120/1/60	16.3	125°F	1500	48" x 15.9" x 15.1"	145
HC120236	12,000	230/1/60	8.12	125°F	1500	48" x 15.9" x 15.1"	145
HC120486	12,000	480/1/60	4.5 approx	125°F	1500	56.6" x 15.9" x 15.1"	205
HC155236	15,000	230/1/60	8.41	125°F	1500	48" x 15.9" x 15.1"	145
HC155486	15,000	480/1/60	4.8 approx	125°F	1500	56.6" x 15.9" x 15.1"	205
HC200236	20,000	230/1/60	11.27	125°F	1500	56.1" x 23.4" x 15.2"	186
HC200486	20,000	480/1/60	6.2 approx	125°F	1500	65.7" x 23.4" x 15.2"	235

Due to design and part development, all information is subject to change

