



**ACCESSORIES**

**HAZARDOUS DUTY ENCLOSURE AIR CONDITIONING SYSTEMS**



**UNITS AVAILABLE WITH HAZ LOC**

MODEL	UL LISTED FOR HAZ LOC	BTU/HOUR	VOLT-AGE/ PHASE/ Hz.
NE020126	PENDING	2000	120/1/60
NE020236	PENDING	2000	230/1/60
NE020486	PENDING	2000	480/1/60
NE030126	PENDING	3000	120/1/60
NE030236	PENDING	3000	230/1/60
NE030486	PENDING	3000	480/1/60
NE040126	PENDING	4000	120/1/60
NE040236	PENDING	4000	230/1/60
NE040486	PENDING	4000	480/1/60
NE050126	PENDING	5000	120/1/60
NE050236	YES	5000	230/1/60
NE050486	YES	5000	480/1/60
NE060126	YES	6000	120/1/60
NE060236	YES	6000	230/1/60
NE060486	YES	6000	480/1/60
NE080126	YES	8000	120/1/60
NE080236	YES	8000	230/1/60
NE080486	YES	8000	480/1/60
HC100126	PENDING	10,000	120/1/60
HC100236	PENDING	10,000	230/1/60
HC100486	PENDING	10,000	480/1/60
HC120126	PENDING	12,000	120/1/60
HC120236	PENDING	12,000	230/1/60
HC120486	PENDING	12,000	480/1/60
HC155236	PENDING	15,000	230/1/60
HC155486	PENDING	15,000	480/1/60
HC200236	PENDING	20,000	230/1/60
HC200486	PENDING	20,000	480/1/60

The Thermal Edge Hazardous Location units are in conformance with all requirements of UL and CUL for Class 1, Division 2, Groups B, C, and D and will meet or exceed all of the specifications for Zone 2, IIC, T3 areas.

- SYSTEM FEATURES:**
- Built in fully active Condensate Evaporation Package changes condensate back to vapor
  - Models range from 2000 to 20,000 BTUH
  - Available in NEMA type 12, 4 and 4X



Due to continuous product development specifications can change without notice