



20,000 BTUH

Indoor/Outdoor, NEMA Types 12, 4 & 4X Available

Engineered & manufactured to endure the most difficult of environments and applications. Thermal Edge air conditioners will exceed environmental requirements in applications like *Steel, Food Processing, Petro-Chemical, Cement, Paper & Pulp and Plastics.*

**Options:**

- External Alarm Capabilities
- Corrosive Environment Package
- Low Ambient Packages
- Dry Contact Remote Monitoring Options
- Integrated Enclosure Heat System
- Cooling Capacity's of 1000 to 20,000 BTUH
- Hazardous Location Package

Digital Temperature Controller

- Programmable set point and temperature operating controls
- Visible Error and/or alarm messaging
- System status indication
- Password protection

Active Condensate Management System

- Complete elimination of condensate
- Eradicates condensate without corrosive contact with coils

Unit Efficiency

- Pressure operated blower control reduces power inrush and saves energy
- Highly efficient rotary compressor
- Fully insulated & sealed cabinet
- Temperature Control Valve to provide a broad temperature range while maintaining cooling capacity.

Industrial Construction

- Free standing rigid chassis eases installation and maintenance

Compressor Protection System

- High & Low refrigerant cutouts with fault indication
- Compressor anti short cycle protection
- Compressor run capacitors reduce power inrush, save energy and increase compressor life

UL File # SA32252



| Model | BTU/Hour | Voltage/Hz. | Running Amps | Max. Ambient Temperature | H x W x D | Ship Weight Lbs. |
|----------|----------|-------------|--------------|--------------------------|-----------------------|------------------|
| HC200236 | 20,000 | 230/1/60 | 11.75 | 125°F | 56.09" x 23" x 15.03" | 186 |
| HC200486 | 20,000 | 480/1/60 | 6.2 | 125°F | 65.7" x 23" x 15.03" | 235 |

All information subject to change without notice

Get the Edge...Get Thermal Edge