



8000 BTUH

Indoor/Outdoor, NEMA Types 12, 4 &amp; 4X Available

Engineered & manufactured to endure the most difficult of environments and applications. Thermal Edge air conditioners will exceed environmental requirements in applications like *Steel, Food Processing, Petro-Chemical, Cement, Paper & Pulp and Plastics.*



This unit  
will fit  
onto a 12"  
Enclosure



UL File # SA32252

#### Digital Temperature Controller

- Programmable set point and temperature operating controls
- Visible Error and/or alarm messaging
- System status indication
- Password protection

#### Active Condensate Management System

- Complete elimination of condensate
- Eradicates condensate without corrosive contact with coils

#### Unit Efficiency

- Pressure operated blower control reduces power inrush and saves energy
- Highly efficient rotary compressor
- Fully insulated & sealed cabinet
- Temperature Control Valve to provide a broad temperature range while maintaining cooling capacity.

#### Industrial Construction

- Free standing rigid chassis eases installation and maintenance

#### Compressor Protection System

- High & Low refrigerant cutouts with fault indication
- Compressor anti short cycle protection
- Compressor run capacitors reduce power inrush, save energy and increase compressor life

#### Options:

- External Alarm Capabilities
- Extended Warranty Available
- Corrosive Environment Package
- High and Low Ambient Packages
- Dry Contact Remote Monitoring Options
- Enclosure Heater System
- Hazardous Environment Units Available
- Cooling Capacity's of 1000 to 20,000 BTUH

Model	BTU/Hour	Voltage Phase Hz.	Running Amps	Max. Ambient Temperature	H x W x D	Ship Weight Lbs.
NE080126-12	8000	120V/1/60	8.70	125°F	36" x 11.8" x 15.02"	100
NE080126-04	8000	120V/1/60	8.70	125°F	36" x 11.8" x 15.02"	100
NE080126-4X	8000	120V/1/60	8.70	125°F	36" x 11.8" x 15.02"	100
NE080236-12	8000	230V/1/60	5.05	125°F	36" x 11.8" x 15.02"	100
NE080236-04	8000	230V/1/60	5.05	125°F	36" x 11.8" x 15.02"	100
NE080236-4X	8000	230V/1/60	5.05	125°F	36" x 11.8" x 15.02"	100
NE080486-12	8000	480V/1/60	2.8	125°F	44.63" x 11.8" x 15.02"	140
NE080486-04	8000	480V/1/60	2.8	125°F	44.63" x 11.8" x 15.02"	140
NE080486-4X	8000	480V/1/60	2.8	125°F	44.63" x 11.8" x 15.02"	140

All information subject to change without notice

*Get the Edge...Get Thermal Edge*